

REVOLT ADVANCED 1



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Midnight Moon
RAM	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SADELSTOLPE	Post Moderne, dropper, 30.9mm, 30mm suspension XS:295mm, S:345mm, M:345mm, M/L:345mm, L:395mm, XL:395mm
SADEL	Giant Grit
DRIVLINA	
VÄXLAR	SRAM Apex 1, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM Apex XPLR
BROMSAR	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BROMSSPAKAR	SRAM Apex 1, left lever dropper switch
KASSETT	SRAM PG-1231, 12-speed, 11x44
KEDJA	SRAM Apex D1
VEVPARTI	SRAM Apex 1 Wide DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant P-X2, alloy
NAV	Giant alloy, 12mm thru-axle
EKRAR	Sapim
DÄCK	Crosscut Grip 45c
EXTRAFUNKTIONER	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 40 990,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Längd sadelrör (mm)	450	470	490	510	530
Seat Post Insertion Depth (mm)	308	323	363	375	375
Vinkel sadelrör	73,5°	73,5°	73,0°	73,0°	73,0°
Topprörets längd (mm)	550	560	575	585	600
Styrhuvud Längd (mm)	135	150	165	180	195
Vinkel styrhuvud	71,0°	71,5°	72,0°	72,0°	72,0°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	72 75	68 72	65 68	65 68	65 68
Hjulbas (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066
Kedjestagslängd (mm)	425 435	425 435	425 435	425 435	425 435
Nedre fäste Drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Stå över höjden (mm)	740 747	757 764	774 780	791 797	807 814
Styrets bredd (mm)	420	440	440	460	460
Stamlängd (mm)	60	70	80	80	90
Vevlängd (mm)	170	172,5	172,5	175	175

All specifications listed are subject to change without notice.