

# REVOLT ADVANCED 2



## SPECS

| FRAME                   |  |
|-------------------------|--|
| <b>SIZES</b>            | XS, S, M, M/L, L, XL   |
| <b>COLOURS</b>          | Panther  |
| <b>FRAME</b>            | Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout                      |
| <b>FORK</b>             | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc           |
| <b>SHOCK</b>            | N/A  |
| COMPONENTS              |  |
| <b>HANDLEBAR</b>        | Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm         |
| <b>GRIPS</b>            | Stratus Lite 3.0   |
| <b>STEM</b>             | Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm                 |
| <b>SEATPOST</b>         | Giant D-Fuse, composite, 14mm offset   |
| <b>SADDLE</b>           | Giant Approach   |
| <b>PEDALS</b>           | N/A  |
| DRIVETRAIN              |  |
| <b>SHIFTERS</b>         | Shimano GRX RX-610, 2x12   |
| <b>FRONT DERAILLEUR</b> | Shimano GRX RX-820   |
| <b>REAR DERAILLEUR</b>  | Shimano GRX RX-820   |
| <b>BRAKES</b>           | Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm                          |
| <b>BRAKE LEVERS</b>     | Shimano GRX RX-610 hydraulic   |
| <b>CASSETTE</b>         | Shimano CS-HG710, 12-speed, 11x36  |
| <b>CHAIN</b>            | KMC X12L-1   |
| <b>CRANKSET</b>         | FSA Omega Modular AGX+, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| <b>BOTTOM BRACKET</b>   | FSA Mega EXA   |

| WHEELS        |  |
|---------------|--|
| <b>RIMS</b>   | Giant P-X2 Disc wheelset, alloy  |
| <b>HUBS</b>   | Giant alloy, 12mm thru-axle  |
| <b>SPOKES</b> | Sapim  |
| <b>TIRES</b>  | Maxxis Rambler, 700x40c, tubeless  |
| <b>EXTRAS</b> | Tubeless prepared, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position |

**Price: \$3,499.00**

## GEOMETRY

| FRAME                    | XS                 | S           | M           | ML          | L           | XL         |
|--------------------------|--------------------|-------------|-------------|-------------|-------------|------------|
|                          | SHORT   LONG SHORT | LONG SHORT  | LONG SHORT  | LONG SHORT  | LONG SHORT  | LONG SHORT |
| Seat Tube Length (mm)    | 430                | 450         | 470         | 490         | 510         | 530        |
| Seat Tube Angle          | 74.0°              | 73.5°       | 73.5°       | 73.0°       | 73.0°       | 73.0°      |
| Top Tube Length (mm)     | 540                | 550         | 560         | 575         | 585         | 600        |
| Head Tube Length (mm)    | 125                | 135         | 150         | 165         | 180         | 195        |
| Head Tube Angle          | 70.0°              | 71.0°       | 71.5°       | 72.0°       | 72.0°       | 72.0°      |
| Fork Rake (mm)           | 50                 | 50          | 50          | 50          | 50          | 50         |
| Trail (mm)               | 78   82            | 72   75     | 68   72     | 65   68     | 65   68     | 65         |
| Wheelbase (mm)           | 1024   1034        | 1020   1030 | 1026   1036 | 1031   1041 | 1041   1051 | 1051       |
| Chain Stay Length (mm)   | 425   435          | 425   435   | 425   435   | 425   435   | 425   435   | 425        |
| Bottom Bracket Drop (mm) | 80   81            | 80   81     | 80   81     | 80   81     | 80   81     | 80         |
| Stack (mm)               | 556                | 570         | 586         | 602         | 616         | 630        |
| Reach (mm)               | 381                | 381         | 387         | 391         | 397         | 407        |
| Stand Over Height (mm)   | 7241   731         | 740   747   | 757   764   | 774   780   | 791   797   | 807        |
| Stem Length (mm)         | 50                 | 60          | 70          | 80          | 80          | 90         |
| Crank Length (mm)        | 170                | 170         | 172.5       | 172.5       | 175         | 175        |
| Wheel Size               | 700C               | 700C        | 700C        | 700C        | 700C        | 700C       |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.