

REVOLT ADVANCED 2



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Golden Haze, Panther
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELPEN	Giant D-Fuse, composite, 14mm offset
ZADEL	Giant Approach
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano GRX RX-610, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
AANDRIJVING	KMC X12L-1
CRANKSET	FSA Omega Modular AGX+, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	FSA BB-AL86 or Shimano Press Fit

WIELSET	
VELGEN	Giant P-X2 Disc wheelset, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Maxxis Rambler/Ravager, 700x40c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Adviesprijs: € 2.899,00

GEOMETRIE

FRAME	S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	450	470	490	510	530					
Zitbuis Hoek	73,5°	73,5°	73,0°	73,0°	73,0°					
Frame Lengte (horizontaal) (mm)	550	560	575	585	600					
Balhoofdbuis Lengte (mm)	135	150	165	180	195					
Balhoofdbuis Hoek	71,0°	71,5°	72,0°	72,0°	72,0°					
Vork Sprong (mm)	50	50	50	50	50					
Naloop (mm)	72 75	68 72	65 68	65 68	65 68					
Wielbasis (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066					
Liggende achtervork lengte (mm)	425 435	425 435	425 435	425 435	425 435					
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81					
Stack (mm)	570	586	602	616	630					
Reach (mm)	381	387	391	397	407					
Stand Over Height (mm)	740 747	757 764	774 780	791 797	807 814					
Stuur breedte (mm)	420	440	440	460	460					
Stuurpen Lengte (mm)	60	70	80	80	90					
Cranklengte (mm)	170	172,5	172,5	175	175					
Wielmaat	700C	700C	700C	700C	700C					

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.