

REVOLT ADVANCED 2

GIANT



SPECIFICATIES

| FRAME            |                                                                                          |
|------------------|------------------------------------------------------------------------------------------|
| MATEN            | S, M, M/L, L, XL                                                                         |
| KLEUREN          | Lavender Blush, Carbon                                                                   |
| FRAME            | Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage |
| VOORVORK         | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc         |
| ONDERDELEN       |                                                                                          |
| STUUR            | Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm       |
| HANDVATTEN       | Stratus Lite 3.0                                                                         |
| STUURPEN         | Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm   |
| ZADELPEN         | Giant D-Fuse, composite, 14mm offset                                                     |
| ZADEL            | Giant Grit                                                                               |
| AFMONTAGE        |                                                                                          |
| SHIFTERS         | Shimano GRX RX-610, 2x12                                                                 |
| VOORDERAILLEUR   | Shimano GRX RX-820                                                                       |
| ACHTERDERAILLEUR | Shimano GRX RX-820                                                                       |
| REMMEN           | Shimano BR-RX410hydraulic, Giant MPH rotors [F]160mm, [R]160mm                           |
| REMHENDELS       | Shimano GRX RX-610 hydraulic                                                             |
| CASSETTE         | Shimano CS-HG710, 12-speed, 11x36                                                        |
| AANDRIJVING      | KMC X12L-1                                                                               |
| CRANKSET         | Shimano FC-RX610-2, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm   |
| BOTTOM BRACKET   | Shimano, press fit                                                                       |

| WIELSET                 |                                                                                                                                            |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| VELGEN                  | Giant P-X2 , alloy                                                                                                                         |
| NAVEN                   | Giant alloy, 12mm thru-axle                                                                                                                |
| SPAKEN                  | Sapim                                                                                                                                      |
| BANDEN                  | Giant Crosscut Grip, 700x45c, tubeless                                                                                                     |
| EXTRA'S                 | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag |
| LIMITS                  |                                                                                                                                            |
| MAXIMALE BANDENVRIJHEID | 53mm                                                                                                                                       |

Adviesprijs: € 2.999,00

GEOMETRIE

| FRAME                           | S                  | M                       | ML                      | L                       | XL                      |
|---------------------------------|--------------------|-------------------------|-------------------------|-------------------------|-------------------------|
|                                 | SHORT   LONG SHORT | LONG SHORT   LONG SHORT | LONG SHORT   LONG SHORT | LONG SHORT   LONG SHORT | LONG SHORT   LONG SHORT |
| Zitbuis Lengte (mm)             | 450                | 470                     | 490                     | 510                     | 530                     |
| Seat Post Insertion Depth (mm)  | 308                | 323                     | 363                     | 375                     | 375                     |
| Zitbuis Hoek                    | 73,5°              | 73,5°                   | 73,0°                   | 73,0°                   | 73,0°                   |
| Frame Lengte (horizontaal) (mm) | 550                | 560                     | 575                     | 585                     | 600                     |
| Balhoofdbuis Lengte (mm)        | 135                | 150                     | 165                     | 180                     | 195                     |
| Balhoofdbuis Hoek               | 71,0°              | 71,5°                   | 72,0°                   | 72,0°                   | 72,0°                   |
| Vork Sprong (mm)                | 50                 | 50                      | 50                      | 50                      | 50                      |
| Naloop (mm)                     | 72   75            | 68   72                 | 65   68                 | 65   68                 | 65   68                 |
| Wielbasis (mm)                  | 1020   1030        | 1026   1036             | 1031   1041             | 1041   1051             | 1056   1066             |
| Liggende achtervork lengte (mm) | 425   435          | 425   435               | 425   435               | 425   435               | 425   435               |
| Bottom Bracket Drop (mm)        | 80   81            | 80   81                 | 80   81                 | 80   81                 | 80   81                 |
| Stack (mm)                      | 570                | 586                     | 602                     | 616                     | 630                     |
| Reach (mm)                      | 381                | 387                     | 391                     | 397                     | 407                     |
| Stand Over Height (mm)          | 740   747          | 757   764               | 774   780               | 791   797               | 807   814               |
| Stuur breedte (mm)              | 420                | 440                     | 440                     | 460                     | 460                     |
| Stuurpen Lengte (mm)            | 60                 | 70                      | 80                      | 80                      | 90                      |
| Cranklengte (mm)                | 170                | 172,5                   | 172,5                   | 175                     | 175                     |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.