

REVOLT ADVANCED 2

GIANT



SPECIFICATIES

| FRAME | |
|------------------|--|
| MATEN | S, M, M/L, L, XL |
| KLEUREN | Carbon, Lavender Blush |
| FRAME | Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage |
| VOORVORK | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc |
| ONDERDELEN | |
| STUUR | Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm |
| HANDVATTEN | Stratus Lite 3.0 |
| STUURPEN | Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm |
| ZADELLEN | Giant D-Fuse, composite, 14mm offset |
| ZADEL | Giant Grit |
| AFMONTAGE | |
| SHIFTERS | Shimano GRX RX-610, 2x12 |
| VOORDERAILLEUR | Shimano GRX RX-820 |
| ACHTERDERAILLEUR | Shimano GRX RX-820 |
| REMMEN | Shimano BR-RX410hydraulic, Giant MPH rotors [F]160mm, [R]160mm |
| REMHENDELS | Shimano GRX RX-610 hydraulic |
| CASSETTE | Shimano CS-HG710, 12-speed, 11x36 |
| AANDRIJVING | KMC X12L-1 |
| CRANKSET | Shimano FC-RX610-2, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | Shimano, press fit |

| WIELSET | |
|--------------------|--|
| VELGEN | Giant P-X2, alloy |
| NAVEN | Giant alloy, 12mm thru-axle |
| SPAKEN | Sapim |
| BANDEN | Giant Crosscut Grip, 700x45c, tubeless |
| EXTRA'S | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag |
| LIMITS | |
| MAX TIRE CLEARANCE | 53mm |

Adviesprijs: € 2.999,00

GEOMETRIE

| FRAME | S | M | ML | L | XL |
|---------------------------------|-------------|-------------|-------------|-------------|-------------|
| | SHORT | LONG SHORT | LONG SHORT | LONG SHORT | LONG SHORT |
| Zitbuis lengte (mm) | 450 | 470 | 490 | 510 | 530 |
| Zitbuis hoek | 73,5° | 73,5° | 73,0° | 73,0° | 73,0° |
| Frame Lengte (horizontaal) (mm) | 550 | 560 | 575 | 585 | 600 |
| Balhoofdbuis Lengte (mm) | 135 | 150 | 165 | 180 | 195 |
| Balhoofdbuis Hoek | 71,0° | 71,5° | 72,0° | 72,0° | 72,0° |
| Vork Sprong (mm) | 50 | 50 | 50 | 50 | 50 |
| Naloop (mm) | 72 75 | 68 72 | 65 68 | 65 68 | 65 68 |
| Wielbasis (mm) | 1020 1030 | 1026 1036 | 1031 1041 | 1041 1051 | 1056 1066 |
| Liggende achtervork lengte (mm) | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 |
| Bottom Bracket Drop (mm) | 80 81 | 80 81 | 80 81 | 80 81 | 80 81 |
| Stack (mm) | 570 | 586 | 602 | 616 | 630 |
| Reach (mm) | 381 | 387 | 391 | 397 | 407 |
| Stand Over Height (mm) | 740 747 | 757 764 | 774 780 | 791 797 | 807 814 |
| Stuur breedte (mm) | 420 | 440 | 440 | 460 | 460 |
| Stuurpen Lengte (mm) | 60 | 70 | 80 | 80 | 90 |
| Cranklengte (mm) | 170 | 172,5 | 172,5 | 175 | 175 |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.