



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Carbon / Solar Flare
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse, composite, 14mm offset
SEDEŽ	Giant Grit
POGON	
PRESTAVNE ROČICE	Shimano GRX RX-610, 2x12
PREDNJI MENJALNIK	Shimano GRX RX-820
ZADNJI MENJALNIK	Shimano GRX RX-820
ZAVORE	Shimano GRX RX-400 HRD, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano GRX RX-610 hydraulic
VERIŽNIK	Shimano CS-HG710, 12-speed, 11x36
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	FSA Omega Modular AGX+, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	FSA BB-AL86, press fit

OBROČNIKI	
OBROČI	Giant P-X2 Disc wheelset, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Giant Crosscut Grip TR, 700x40c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

## GEOMETRIJA

OKVIR	XS		S		M		ML		L
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	
Dolžina sedežne cevi (mm)	430	450	450	470	470	490	490	510	530
Kot sedežne cevi	74,0°	73,5°	73,5°	73,5°	73,5°	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	550	560	560	575	575	590	600
Višina glave okvirja (mm)	125	135	135	150	150	165	165	180	190
Krmilni kot	70,0°	71,0°	71,0°	71,5°	71,5°	72,0°	72,0°	72,0°	72,0°
Zamik vpetja osi (mm)	50	50	50	50	50	50	50	50	50
Trail (mm)	78   82	72   75	72   75	68   72	68   72	65   68	65   68	65   68	65   68
Medosna razdalja (mm)	1024   1034	1020   1030	1020   1030	1026   1036	1026   1036	1031   1041	1031   1041	1031   1041	1031   1041
Dolžina cevi ob verigi (mm)	425   435	425   435	425   435	425   435	425   435	425   435	425   435	425   435	425   435
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81	80   81	80   81	80   81	80   81
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	570	586	586	602	602	618	634
Doseg (mm)	381	381	381	387	387	391	391	397	403
Višina zgornje cevi (mm)	724   731	740   747	740   747	757   764	757   764	774   780	774   780	791   797	808   814
Širina krmila (mm)	420	420	420	440	440	440	440	460	460
Dolžina opore krmila (mm)	50	60	60	70	70	80	80	90	90
Dolžina gonilke (mm)	170	170	170	172,5	172,5	172,5	172,5	172,5	172,5
Velikost obročnikov	700c	700c	700c	700c	700c	700c	700c	700c	700c

Vse navedene specifikacije se lahko spremenijo brez obvestila.