

REVOLT ADVANCED 3

GIANT



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, M/L, L, XL
ΧΡΩΜΑΤΑ	Aquarium
ΣΚΕΛΕΤΟΣ	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
ΠΙΡΟΥΝΙ	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
ΕΞΑΡΤΗΜΑΤΑ	
TIMONI	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	Giant D-Fuse, composite, 14mm offset
ΣΕΛΛΑ	Giant Grit
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano CUES U6030, 1x11
ΝΤΕΡΑΓΓΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΓΕΡ ΟΠΙΣΘΙΟ.	Shimano CUES U6000
ΦΡΕΝΑ	Shimano CUES U6030 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
ΜΑΝ'ΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano CUES U6030 hydraulic
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano CS-LG400, 11x50
ΑΛΥΣΙΔΑ	KMC X11
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Shimano FC-U6030-1, 42t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant P-X2 , alloy
KENTPA	Giant alloy, 12mm thru-axle
AKTINEΣ	Sapim
ΕΛΑΣΤΙΚΑ	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	430	450	470	490	510
Seat Post Insertion Depth (mm)	294	308	323	363	375
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585
Head Tube Length (mm)	125	135	150	165	180
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797
Handlebar Width (mm)	420	420	440	440	460
Stem Length (mm)	50	60	70	80	80
Crank Length (mm)	170	170	172,5	172,5	175

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση