

REVOLT ADVANCED 3



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Aquarium
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse, composite, 14mm offset
SEDEŽ	Giant Grit
POGON	
PRESTAVNE ROČICE	Shimano CUES U6030, 1x11
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano CUES U6000
ZAVORE	Shimano CUES U6030 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano CUES U6030 hydraulic
VERIŽNIK	Shimano CS-LG400, 11x50
VERIGA	KMC X11
GONILKE Z VERIŽNIKI	Shimano FC-U6030-1, 42t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant P-X2, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Giant Crosscut Grip, 700x45c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS		S		M		ML	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Dolžina sedežne cevi (mm)	430	450	470	490	510	530	550	570
Seat Post Insertion Depth (mm)	294	308	323	363	391	425	450	480
Kot sedežne cevi	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	590	605	620	635
Višina glave okvirja (mm)	125	135	150	165	180	195	210	225
Krnilni kot	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°	72,0°	72,0°
Zamik vpetja osi (mm)	50	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	62 65	59 62	56 59	53 56
Medosna razdalja (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1036 1046	1041 1051	1046 1056	1051 1061
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	586	602	617	632	647	662
Doseg (mm)	381	381	387	391	396	400	404	408
Višina zgornje cevi (mm)	724 731	740 747	757 764	774 780	791 798	808 815	825 832	842 849
Širina krmila (mm)	420	420	440	440	460	460	480	480
Dolžina opore krmila (mm)	50	60	70	80	90	100	110	120
Dolžina gonilke (mm)	170	170	172,5	172,5	175	175	177,5	177,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.