

REVOLT ADVANCED 3



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Panther
RAM	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SADELSTOLPE	Giant D-Fuse, composite, 14mm offset
SADEL	Giant Grit
DRIVLINJA	
VÄXLAR	Shimano GRX RX-400, 2x10
FRAMVÄXEL	Shimano GRX-RX400
BAKVÄXEL	Shimano GRX-RX400
BROMSAR	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BROMSSPAKAR	Shimano GRX RX-400 hydraulic
KASSETT	Shimano Tiagra, 11x34
KEDJA	KMC X10-1
VEVPARTI	FSA Omega, 30/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BROMSREGLAGE	FSA BB-AL86, press fit

HJUL	
FÄLGAR	Giant P-X2 Disc wheelset, alloy
NAV	Giant alloy, 12mm thru-axle
EKRAR	Sapim
DÄCK	Giant Crosscut Grip TR, 700x40c, tubeless
EXTRAFUNKTIONER	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 30 590,00 kr

GEOMETRY

RAM		ML
		SHORT LONG
Längd sadelrör (mm)		490
Vinkel sadelrör		73,0°
Topprörets längd (mm)		575
Styrhuvud Längd (mm)		165
Vinkel styrhuvud		72,0°
Gaffelvinkel (mm)		50
Spår (mm)		65 68
Hjulbas (mm)		1031 1041
Kedjestagslängd (mm)		425 435
Nedre fäste Drop (mm)		80 81
Stack (mm)		602
Reach (mm)		391
Stå över höjden (mm)		774 780
Styrets bredd (mm)		440
Stamlängd (mm)		80
Vevlängd (mm)		172,5
Hjulstorlek		700c

All specifications listed are subject to change without notice.