# REVOLT ADVANCED PRO 0



## СПЕЦИФИКАЦИИ

| РАМКА | |
|---|---|
| **РАЗМЕР** | XS, S, M, M/L, L, XL |
| **ЦВЯТ** | Interstellar/Chrome |
| **РАМКА** | Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage |
| **ВИЛКА** | Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc |
| **КОМПОНЕНТИ** | |
| **КОРМИЛО** | Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm |
| **ГРИПОВЕ** | Stratus Lite 3.0 |
| **ЛАПА** | Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm |
| **КОЛЧЕ ЗА СЕДАЛКА** | Giant D-Fuse SLR, composite, -5/+15mm offset |
| **СЕДАЛКА** | Giant Grit SL |
| **DRIVETRAIN** | |
| **КОМАНДИ** | SRAM Force eTap AXS, 2x12 |
| **ПРЕДЕН ДЕРАЙЛЬОР** | SRAM Force eTap AXS |
| **ЗАДЕН ДЕРАЙЛЬОР** | SRAM Force eTap AXS |
| **СПИРАЧКИ** | SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm |
| **РЪКОХВАТКИ ЗА СПИРАЧКИ** | SRAM Force eTap AXS hydraulic |
| **КАСЕТА** | SRAM Force, 12-speed, 10x36 |
| **ВЕРИГА** | SRAM Force D1 |
| **КУРБЕЛ** | SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| **СРЕДНА КАСЕТА** | SRAM DUB, press fit |

| КАПЛИ | |
|---|---|
| **ШИНИ** | Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm |
| **ГЛАВИНИ** | [F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle |
| **СПИЦИ** | Sapim CX-Ray |
| **ГУМИ** | CADEX GX, 700x40c, tubeless |
| **ЕКСТРИ** | tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag |
| **ЛИМИТИ** | |
| **MAX TIRE CLEARANCE** | 53mm |

## ГЕОМЕТРИЯ

| РАМКА | XS | S | M | ML | L | X |
|---|---|---|---|---|---|---|
| | SHORT \| LONG | SHORT \| LONG | SHORT \| LONG | SHORT \| LONG | SHORT \| LONG | SH |
| Seat Tube Length (mm) | 430 | 450 | 470 | 490 | 510 | 53 |
| Seat Tube Angle | 74,0° | 73,5° | 73,5° | 73,0° | 73,0° | 73 |
| Top Tube Length (mm) | 540 | 550 | 560 | 575 | 585 | 60 |
| Head Tube Length (mm) | 125 | 135 | 150 | 165 | 180 | 19 |
| Head Tube Angle | 70,0° | 71,0° | 71,5° | 72,0° | 72,0° | 72 |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 78 \| 82 | 72 \| 75 | 68 \| 72 | 65 \| 68 | 65 \| 68 | 65 |
| Wheelbase (mm) | 1024 \| 1034 | 1020 \| 1030 | 1026 \| 1036 | 1031 \| 1041 | 1041 \| 1051 | 10 |
| Chain Stay Length (mm) | 425 \| 435 | 425 \| 435 | 425 \| 435 | 425 \| 435 | 425 \| 435 | 42 |
| Bottom Bracket Drop (mm) | 80 \| 81 | 80 \| 81 | 80 \| 81 | 80 \| 81 | 80 \| 81 | 80 |
| Stack (mm) | 556 | 570 | 586 | 602 | 616 | 63 |
| Обсег (mm) | 381 | 381 | 387 | 391 | 397 | 40 |
| Stand Over Height (mm) | 724 \| 731 | 740 \| 747 | 757 \| 764 | 774 \| 780 | 791 \| 797 | 80 |
| Ширина на Кормило (mm) | 420 | 420 | 440 | 440 | 460 | 46 |
| Дължина на Лапа (mm) | 50 | 60 | 70 | 80 | 80 | 90 |
| Дължина на Курбел (mm) | 170 | 170 | 172,5 | 172,5 | 175 | 17 |
| Размер на Каплите | 700c | 700c | 700c | 700c | 700c | 70 |

*All specifications listed are subject to change without notice.*