

# REVOLT ADVANCED PRO 0

**GIANT**



## СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, M/L, L, XL
ЦВЯТ	Cyber Lime
РАМКА	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
ВИЛКА	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
ГРИПОВЕ	Stratus Lite 3.0
ЛАПА	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
КОЛЧЕ ЗА СЕДАЛКА	Giant D-Fuse SLR, composite, -5/+15mm offset
СЕДАЛКА	Giant Grit SL
ПЕДАЛИ	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
DRIVETRAIN	
КОМАНДИ	SRAM Force AXS E1, 2x12
ПРЕДЕН ДЕРАЙЛЪОР	SRAM Force AXS D2
ЗАДЕН ДЕРАЙЛЪОР	SRAM Force AXS E1
СПИРАЧКИ	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	SRAM Force AXS E1 hydraulic
КАСЕТА	SRAM Force E1, 12-speed, 10x36
ВЕРИГА	SRAM Force E1
КУРБЕЛ	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
ГЛАВИНИ	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
СПИЦИ	Sapim CX-Ray
ГУМИ	CADEX GX, 700x40c, tubeless
ЕКСТРИ	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
ЛИМИТИ	
MAX TIRE CLEARANCE	53mm

## ГЕОМЕТРИЯ

РАМКА	XS	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	190
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78   82	72   75	68   72	65   68	65   68	65   68
Wheelbase (mm)	1024   1034	1020   1030	1026   1036	1031   1041	1041   1051	1041   1051
Chain Stay Length (mm)	425   435	425   435	425   435	425   435	425   435	425   435
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81	80   81
Stack (mm)	556	570	586	602	616	630
Обсер (mm)	381	381	387	391	397	400
Stand Over Height (mm)	724   731	740   747	757   764	774   780	791   797	800   800
Ширина на Кормило (mm)	420	420	440	440	460	460
Дължина на Лапа (mm)	50	60	70	80	80	90
Дължина на Курбел (mm)	170	170	172,5	172,5	175	175

All specifications listed are subject to change without notice.