



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Cyber Lime
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
GABEL	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse SLR, composite, -5/+15mm offset
SATTEL	Giant Grit SL
PEDALE	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
ANTRIEB	
SCHALTHEBEL	SRAM Force AXS E1, 2x12
UMWERFER	SRAM Force AXS D2
SCHALTWERK	SRAM Force AXS E1
BREMSEN	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BREMSHEBEL	SRAM Force AXS E1 hydraulic
KASSETTE	SRAM Force E1, 12-speed, 10x36
KETTE	SRAM Force E1
KURBEL	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
NABE	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim CX-Ray
REIFEN	CADEX GX, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

## GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
	SHORT   LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Sitzrohrlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	540	550	560	575	585	600
Steuerrohr-Länge (mm)	125	135	150	165	180	195
Steuerrohr-Winkel	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	78   82	72   75	68   72	65   68	65   68	65
Radstand (mm)	1024   1034	1020   1030	1026   1036	1031   1041	1041   1051	1051
Kettenstrebene-Länge (mm)	425   435	425   435	425   435	425   435	425   435	425
Tretlager-Höhe (mm)	80   81	80   81	80   81	80   81	80   81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Überstandshöhe (mm)	724   731	740   747	757   764	774   780	791   797	807
Lenkerbreite (mm)	420	420	440	440	460	460
Vorbaulänge (mm)	50	60	70	80	80	90
Kurbellänge (mm)	170	170	172.5	172.5	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.