



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, M/L, L, XL
ΧΡΩΜΑΤΑ	Interstellar/Chrome
ΣΚΕΛΕΤΟΣ	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
ΠΙΠΟΥΝΙ	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ΛΑΙΜΟΣ ΣΈΛΛΑΣ	Giant D-Fuse SLR, composite, -5/+15mm offset
ΣΈΛΛΑ	Giant Grit SL
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM Force eTap AXS, 2x12
ΝΤΕΡΑΓΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	SRAM Force eTap AXS
ΝΤΕΡΑΓΓΙΕΡ ΟΠΙΣΘΙΟ.	SRAM Force eTap AXS
ΦΡΈΝΑ	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
ΜΑΝ'ΕΤΤΕΣ ΦΡΈΝΩΝ	SRAM Force eTap AXS hydraulic
CASETTE Ή ΕΛΕΥΘΕΡΟ	SRAM Force, 12-speed, 10x36
ΑΛΥΣΙΔΑ	SRAM Force D1
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
ΚΕΝΤΡΑ	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
ΑΚΤΙΝΕΣ	Sapim CX-Ray
ΕΛΑΣΤΙΚΑ	CADEX GX, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	195
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051 1061
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797	807 814
Handlebar Width (mm)	420	420	440	440	460	460
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700c	700c	700c	700c	700c	700c

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση