

REVOLT ADVANCED PRO 0



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Messier
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Giant Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Force eTap AXS, 2x12
FRONT DERAILLEUR	SRAM Force eTap AXS
REAR DERAILLEUR	SRAM Force eTap AXS
BRAKES	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x36
CHAIN	SRAM Force D1
CRANKSET	SRAM Force D1 DUB, 30/43
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 Carbon Disc WheelSystem
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX AR, 700x40c, tubeless
EXTRAS	Tubeless prepared, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position

Price: \$7,999.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	195
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797	807
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.