

REVOLT ADVANCED PRO 0



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Digital Blurple/Iris
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEATPOST	Giant D-Fuse SLR w/ offset -5/+15
SADDLE	Giant Approach SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Sram Force AXS HRD, 2x12
FRONT DERAILLEUR	Sram Force AXS Wide
REAR DERAILLEUR	Sram Force AXS, Max 36T
BRAKES	Sram ForceTap AXS HRD, SRAM CenterLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force AXS HRD (hydraulic road disc)
CASSETTE	Sram Force, XG-1270, 12-speed, 10-36
CHAIN	SRAM FORCE D1, 12-speed
CRANKSET	Sram Force D2 DUB,30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX AR, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Suggested Retail Price (CDN): \$7,299.00

FRAME GEOMETRY

FRAME	XS		S		M		ML		L		XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530	550	570	590	610	630
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600	610	620	630	640	650
Head Tube Length (mm)	125	135	150	165	180	190	200	210	220	230	240
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°	72.0°	72.0°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68	65 68	65 68	65 68	65 68	65 68
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051 1061	1061 1071	1071 1081	1081 1091	1091 1101	1101 1111
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630	644	658	672	686	700
Reach (mm)	381	381	387	391	397	401	405	409	413	417	421
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797	808 814	825 831	842 848	859 865	876 882	893 899
Handlebar Width (mm)	420	420	440	440	460	460	460	460	460	460	460
Stem Length (mm)	50	60	70	80	80	90	90	90	90	90	90
Crank Length (mm)	170	170	172.5	172.5	175	175	175	175	175	175	175
Wheel Size	700C	700C	700C	700C	700C	700C	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.