

# REVOLT ADVANCED PRO 0

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Cyber Lime
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
<b>FORK</b>	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
<b>SEATPOST</b>	Giant D-Fuse SLR, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Grit SL
<b>PEDALS</b>	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force AXS E1, 2x12
<b>FRONT DERAILLEUR</b>	SRAM Force AXS D2
<b>REAR DERAILLEUR</b>	SRAM Force AXS E1
<b>BRAKES</b>	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force AXS E1 hydraulic
<b>CASSETTE</b>	SRAM Force E1, 12-speed, 10x36
<b>CHAIN</b>	SRAM Force E1
<b>CRANKSET</b>	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
<b>HUBS</b>	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim CX-Ray
<b>TYRES</b>	CADEX GX, 700x40c, tubeless
<b>EXTRAS</b>	Tubeless prepared, in-frame storage bag
LIMITS	
<b>MAX TYRE CLEARANCE</b>	53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position with 1x drivetrains. Max tyre size with a 2x drivetrain is 45mm in the long position.

**Price: €5,999.00**

## GEOMETRY

FRAME	S	M	ML	L	XL
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Seat Tube Length (mm)	450	470	490	510	530
Seat Tube Angle	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	550	560	575	585	600
Head Tube Length (mm)	135	150	165	180	195
Head Tube Angle	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	72   75	68   72	65   68	65   68	65   68
Wheelbase (mm)	1020   1030	1026   1036	1031   1041	1041   1051	1056   1066
Chain Stay Length (mm)	425   435	425   435	425   435	425   435	425   435
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Stand Over Height (mm)	740   747	757   764	774   780	791   797	807   814
Handlebar Width (mm)	420	440	440	460	460
Stem Length (mm)	60	70	80	80	90
Crank Length (mm)	170	172.5	172.5	175	175

All specifications listed are subject to change without notice.