

# REVOLT ADVANCED PRO 0



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Cyber Lime
<b>FRAME</b>	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
<b>FORK</b>	Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact Aerolight XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
<b>SEATPOST</b>	Giant D-Fuse SLR, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Grit SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force AXS HRD, ED-Force-E1
<b>FRONT DERAILLEUR</b>	SRAM Force AXS Wide D2
<b>REAR DERAILLEUR</b>	SRAM Force AXS, FD-Force-E1
<b>BRAKES</b>	SRAM Force AXS HRD, ED-Force-E1, SRAM PaceLine X rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force AXS HRD, ED-Force-E1
<b>CASSETTE</b>	SRAM Force E1 XG-1270, 12-speed, 10-36
<b>CHAIN</b>	SRAM Force-E1, 12-speed
<b>CRANKSET</b>	SRAM Force D2 Wide DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, Press Fit

WHEELS	
<b>RIMS</b>	Giant CXR 1 Carbon Disc WheelSystem
<b>HUBS</b>	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim CX-Ray
<b>TIRES</b>	CADEX GX, 700x40c, tubeless
<b>EXTRAS</b>	Tubeless prepared, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position, In frame storage bag
LIMITS	
<b>MAX TIRE CLEARANCE</b>	53mm in "long" position

**Price: \$9,499.00**

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SH
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	190
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78   82	72   75	68   72	65   68	65   68	65
Wheelbase (mm)	1024   1034	1020   1030	1026   1036	1031   1041	1041   1051	1050
Chain Stay Length (mm)	425   435	425   435	425   435	425   435	425   435	425
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	400
Stand Over Height (mm)	724   731	740   747	757   764	774   780	791   797	800
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.