

REVOLT ADVANCED PRO 0



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Cyber Lime
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Giant Grit SL
PEDALS	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
DRIVETRAIN	
SHIFTERS	SRAM Force AXS E1, 2x12
FRONT DERAILLEUR	SRAM Force AXS D2
REAR DERAILLEUR	SRAM Force AXS E1
BRAKES	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force AXS E1 hydraulic
CASSETTE	SRAM Force E1, 12-speed, 10x36
CHAIN	SRAM Force E1
CRANKSET	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX GX, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Recommended Retail Price: **\$7,000.00**

GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SH
Seat Tube Length (inch)	16.9	17.7	18.5	19.3	20.1	20
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73
Top Tube Length (inch)	21.3	21.7	22	22.6	23	23
Head Tube Length (inch)	4.9	5.3	5.9	6.5	7.1	7.7
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72
Fork Rake (inch)	2	2	2	2	2	2
Trail (inch)	3.1 3.2	2.8 3	2.7 2.8	2.6 2.7	2.6 2.7	2.6
Wheelbase (inch)	40.3 40.7	40.2 40.6	40.4 40.8	40.6 41	41 41.4	41
Chain Stay Length (inch)	16.7 17.1	16.7 17.1	16.7 17.1	16.7 17.1	16.7 17.1	16
Bottom Bracket Drop (inch)	3.1 3.2	3.1 3.2	3.1 3.2	3.1 3.2	3.1 3.2	3.1
Stack (inch)	21.9	22.4	23.1	23.7	24.3	24
Reach (inch)	15	15	15.2	15.4	15.6	16
Stand Over Height (inch)	28.5 28.8	29.1 29.4	29.8 30.1	30.5 30.7	31.1 31.4	31
Handlebar Width (inch)	16.5	16.5	17.3	17.3	18.1	18
Stem Length (inch)	2	2.4	2.8	3.1	3.1	3.5
Crank Length (inch)	6.7	6.7	6.8	6.8	6.9	6.9

*All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.