

REVOLT ADVANCED PRO 0

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Cyber Lime
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
HORQUILLA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTES	
MANILLAR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
PUÑOS	Stratus Lite 3.0
POTENCIA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIJA DE SILLÍN	Giant D-Fuse SLR, composite, -5/+15mm offset
SILLÍN	Giant Grit SL
PEDALES	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Force AXS E1, 2x12
DESVIADOR	SRAM Force AXS D2
CAMBIO TRASERO	SRAM Force AXS E1
FRENOS	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	SRAM Force AXS E1 hydraulic
CASSETTE	SRAM Force E1, 12-speed, 10x36
CADENA	SRAM Force E1
JGO. PLATOS Y BIELAS	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
BUJES	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
RADIOS	Sapim CX-Ray
CUBIERTAS	CADEX GX, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	53mm

Precio: 6.999,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Longitud del tubo del sillín (mm)	430	450	470	490	510
Ángulo del tubo del sillín	74,0°	73,5°	73,5°	73,0°	73,0°
Longitud del tubo superior (mm) (mm)	540	550	560	575	585
Longitud del tubo de dirección (mm) (mm)	125	135	150	165	180
Ángulo del tubo de dirección	70,0°	71,0°	71,5°	72,0°	72,0°
Inclinación de la horquilla (mm)	50	50	50	50	50
Trail (mm) (mm)	78 82	72 75	68 72	65 68	65
Distancia entre ejes (mm) (mm)	1024 1034	1020 1030	1026 1036	1031 1041	104
Longitud de la vaina (mm) (mm)	425 435	425 435	425 435	425 435	425
Caída del eje de pedalier (mm) (mm)	80 81	80 81	80 81	80 81	80
Stack (mm) (mm)	556	570	586	602	616
Reach (mm) (mm)	381	381	387	391	397
Altura del suelo al tubo (mm) (mm)	724 731	740 747	757 764	774 780	791
Ancho del manillar (mm) (mm)	420	420	440	440	460
Longitud de la potencia (mm) (mm)	50	60	70	80	80
Longitud de las bielas (mm) (mm)	170	170	172,5	172,5	175

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.