

REVOLT ADVANCED PRO 0

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Dark Red / Grenadine
CUADRO	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
TIJERA	Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
POTENCIA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
POSTE DE ASIENTO	Giant D-Fuse SLR, composite, -5/+15mm offset
ASIENTO	Giant Approach SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano GRX RX-815 Di2, 2x11
DESVIADOR	Shimano GRX RX-815 Di2
CAMBIO TRASERO	Shimano GRX RX-815 Di2
FRENOS	Shimano GRX RX-810 hydraulic, Shimano SM-RT800 rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	Shimano GRX RX-810 hydraulic
CASSETTE	Shimano CS-HG800, 11-speed, 11x34
CADENA	KMC X11SL-1
MULTIPLICACIÓN	Shimano GRX RX-810, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant CXR 1 Carbon Disc WheelSystem
MAZAS	Giant CXR 1 Carbon Disc WheelSystem
RAYOS	Giant CXR 1 Carbon Disc WheelSystem
NEUMÁTICOS	Maxxis Receptor, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 42mm max tire size in "short" flip chip position

Precio: \$144,900.00

GEOMETRÍA

CUADRO	XS	S	M	ML
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Longitud de la Base del Poste de Asiento (mm)	430	450	470	490
Ángulo de la Base del Poste de Asiento	74.0°	73.5°	73.5°	73.0°
Longitud del Tubo Superior (mm)	540	550	560	575
Longitud del Telescopio (mm)	125	135	150	165
Ángulo del Telescopio	70.0°	71.0°	71.5°	72.0°
Rake (mm)	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68
Distancia entre Ejes (mm)	1024 1034	1020 1030	1026 1036	1031 1041
Longitud de Vaina Inferior (mm)	425 435	425 435	425 435	425 435
Caída del Eje de Centro (mm)	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602
Reach (mm)	381	381	387	391
Altura del Tubo Superior al Suelo (mm)	724 731	740 747	757 764	774 780
Ancho del Manubrio (mm)	420	420	440	440
Longitud de la Potencia (mm)	50	60	70	80
Longitud de la Biela (mm)	170	170	172.5	172.5
Tamaño de las Ruedas	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.