

# REVOLT ADVANCED PRO 0



## SPECS

FRAME	
<b>SIZES</b>	S, M, M/L, L, XL
<b>COLOURS</b>	Interstellar/Chrome
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
<b>FORK</b>	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc, flat mount disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XR D-Fuse, 31.8mm S:42cm, M, M/L:44cm, L, XL:46cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact AeroLight, -10 degree
<b>SEATPOST</b>	Giant D-Fuse SLR, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Grit SL *some bikes may be substituted: Giant Approach SL
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force eTap AXS, 2x12
<b>FRONT DERAILLEUR</b>	SRAM Force eTap AXS
<b>REAR DERAILLEUR</b>	SRAM Force eTap AXS
<b>BRAKES</b>	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force eTap AXS
<b>CASSETTE</b>	SRAM Force, 12-speed, 10x36
<b>CHAIN</b>	SRAM Force D1
<b>CRANKSET</b>	SRAM Force D1 DUB, 30/43 S:170mm, M, M/L:172.5mm, L, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant CXR 1 Carbon Disc WheelSystem, 35mm depth, 25mm inner width
<b>HUBS</b>	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim CX-Ray
<b>TIRES</b>	CADEX GX, tubeless, 700x40c, 170 tpi, FOLDING
<b>EXTRAS</b>	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, integrated down tube storage bag
LIMITS	
<b>MAX TIRE CLEARANCE</b>	53mm

**Suggested Retail Price (CDN): \$7,299.00**

## FRAME GEOMETRY

FRAME	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Seat Tube Length (mm)	450	470	490	510	530
Seat Tube Angle	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	550	560	575	585	600
Head Tube Length (mm)	135	150	165	180	195
Head Tube Angle	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	72   75	68   72	65   68	65   68	65   68
Wheelbase (mm)	1020   1030	1026   1036	1031   1041	1041   1051	1056   1066
Chain Stay Length (mm)	425   435	425   435	425   435	425   435	425   435
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Stand Over Height (mm)	740   747	757   764	774   780	791   797	807   814
Handlebar Width (mm)	420	440	440	460	460
Stem Length (mm)	60	70	80	80	90
Crank Length (mm)	170	172.5	172.5	175	175
Wheel Size	700c	700c	700c	700c	700c

*All prices and specifications are subject to change without notice.*