

REVOLT ADVANCED PRO 0

GIANT

SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, M/L, L, XL
BOJE	Cyber Lime
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
VOLAN	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
LULA VOLANA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
CIJEV SJEDALA	Giant D-Fuse SLR, composite, -5/+15mm offset
SJEDALO	Giant Grit SL
PEDALE	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
POGON	
RUČICE MJENJAČA	SRAM Force AXS E1, 2x12
PREDNJI MJENJAČ	SRAM Force AXS D2
STRAŽNJI MJENJAČ	SRAM Force AXS E1
KOČNICE	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
RUČICE KOČNICA	SRAM Force AXS E1 hydraulic
KAZETA	SRAM Force E1, 12-speed, 10x36
LANAC	SRAM Force E1
POGON	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
NABE	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	Sapim CX-Ray
GUME	CADEX GX, 700x40c, tubeless
DODACI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS	S	M
	SHORT LONG	SHORT LONG	SHORT LONG
Dužina cijevi sjedala (mm)	430	450	470
Kut cijevi sjedala	74,0°	73,5°	73,5°
Dužina gornje cijevi (mm)	540	550	560
Dužina prednje cijevi (mm)	125	135	150
Kut vilice	70,0°	71,0°	71,5°
Zakrivljenost vilice (offset) (mm)	50	50	50
Staza (mm)	78 82	72 75	68 72
Međuosovinski razmak kotača (mm)	1024 1034	1020 1030	1026 1036
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	425 435	425 435	425 435
Položaj osovine pogona (mm)	80 81	80 81	80 81
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	556	570	586
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	381	381	387
Prekoračna visina (mm)	724 731	740 747	757 764
Širina volana (mm)	420	420	440
Dužina lule volana (mm)	50	60	70
Dužina poluge pedale (mm)	170	170	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.