

# REVOLT ADVANCED PRO 0

GIANT



## SPECS

TELAIO	
<b>TAGLIE</b>	XS, S, M, M/L, L, XL
<b>COLORAZIONI</b>	Cyber Lime
<b>TELAIO</b>	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
<b>FORCELLA</b>	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTISTICA	
<b>MANUBRIO</b>	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
<b>MANOPOLE</b>	Stratus Lite 3.0
<b>ATTACCO MANUBRIO</b>	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
<b>REGGISELLA</b>	Giant D-Fuse SLR, composite, -5/+15mm offset
<b>SELLA</b>	Giant Grit SL
<b>PEDALI</b>	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
SISTEMA DI TRASMISSIONE	
<b>CAMBIO</b>	SRAM Force AXS E1, 2x12
<b>DERAGLIATORE ANTERIORE</b>	SRAM Force AXS D2
<b>DERAGLIATORE POSTERIORE</b>	SRAM Force AXS E1
<b>FRENI</b>	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
<b>COMANDI FRENO</b>	SRAM Force AXS E1 hydraulic
<b>PACCO PIGNONI</b>	SRAM Force E1, 12-speed, 10x36
<b>CATENA</b>	SRAM Force E1
<b>GUARNITURA</b>	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>MOVIMENTO CENTRALE</b>	SRAM DUB, press fit

RUOTE	
<b>CERCHI</b>	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
<b>MOZZI</b>	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
<b>RAGGI</b>	Sapim CX-Ray
<b>COPERTONI</b>	CADEX GX, 700x40c, tubeless
<b>EXTRA</b>	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITI	
<b>SEZIONE MASSIMA SUPPORTATA</b>	53mm

Prezzo: 6.799,00 €

## GEOMETRIA

TELAIO	XS	S	M	ML	L
	SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LC
Lunghezza Tubo Sella (mm)	430	450	470	490	510
Angolo Tubo Sella	74,0°	73,5°	73,5°	73,0°	73,0°
Lunghezza Tubo Orizzontale (mm)	540	550	560	575	585
Lunghezza Tubo Sterzo (mm)	125	135	150	165	180
Angolo Sterzo	70,0°	71,0°	71,5°	72,0°	72,0°
Rake Forcella (mm)	50	50	50	50	50
Avancorsa (mm)	78   82	72   75	68   72	65   68	65   68
Interasse (mm)	1024   1034	1020   1030	1026   1036	1031   1041	1041   105
Lunghezza Carro Posteriore (mm)	425   435	425   435	425   435	425   435	425   435
Drop Movimento Centrale (mm)	80   81	80   81	80   81	80   81	80   81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Altezza stand over (mm)	724   731	740   747	757   764	774   780	791   797
Larghezza Manubrio c/c (mm)	420	420	440	440	460
Lunghezza Attacco Manubrio (mm)	50	60	70	80	80
Lunghezza Pedivella (mm)	170	170	172,5	172,5	175

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.