

REVOLT ADVANCED PRO 0



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Digital Blurple/Iris
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELPEN	Giant D-Fuse SLR w/ offset -5/+15
ZADEL	Giant Approach SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Sram Force AXS HRD, 2x12
VOORDERAILLEUR	Sram Force AXS Wide
ACHTERDERAILLEUR	Sram Force AXS, Max 36T
REMMEN	Sram ForceTap AXS HRD, SRAM CenterLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Force AXS HRD (hydraulic road disc)
CASSETTE	Sram Force, XG-1270, 12-speed, 10-36
AANDRIJVING	SRAM FORCE D1, 12-speed
CRANKSET	Sram Force D2 DUB,30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAVEN	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim CX-Ray
BANDEN	CADEX AR, 700x40c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Adviesprijs: € 6.799,00

GEOMETRIE

FRAME	S		M		ML		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	450		470		490		510		530	
Zitbuis Hoek	73,5°		73,5°		73,0°		73,0°		73,0°	
Frame Lengte (horizontaal) (mm)	550		560		575		585		600	
Balhoofdbuis Lengte (mm)	135		150		165		180		195	
Balhoofdbuis Hoek	71,0°		71,5°		72,0°		72,0°		72,0°	
Vork Sprong (mm)	50		50		50		50		50	
Naloop (mm)	72 75		68 72		65 68		65 68		65 68	
Wielbasis (mm)	1020 1030		1026 1036		1031 1041		1041 1051		1056 1066	
Liggende achtervork lengte (mm)	425 435		425 435		425 435		425 435		425 435	
Bottom Bracket Drop (mm)	80 81		80 81		80 81		80 81		80 81	
Stack (mm)	570		586		602		616		630	
Reach (mm)	381		387		391		397		407	
Stand Over Height (mm)	740 747		757 764		774 780		791 797		807 814	
Stuur breedte (mm)	420		440		440		460		460	
Stuurpen Lengte (mm)	60		70		80		80		90	
Cranklengte (mm)	170		172,5		172,5		175		175	
Wielmaat	700C		700C		700C		700C		700C	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.