

REVOLT ADVANCED PRO 0



SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	Interstellar/Chrome
CADRU	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FURCA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTE	
GHIDON	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
PIPA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIJA SA	Giant D-Fuse SLR, composite, -5/+15mm offset
SA	Giant Grit SL
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Force eTap AXS, 2x12
SCHIMBATOR FATA	SRAM Force eTap AXS
SCHIMBATOR SPATE	SRAM Force eTap AXS
FRANE	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
MANETE FRANA	SRAM Force eTap AXS hydraulic
PINIOANE	SRAM Force, 12-speed, 10x36
LANT	SRAM Force D1
ANGRENAJ	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
BUTUCI	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPITE	Sapim CX-Ray
ANVELOPE	CADEX GX, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIE

CADRU	XS	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	195
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797	807
Handlebar Width (mm)	420	420	440	440	460	460
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700c	700c	700c	700c	700c	700c

Toate specificatiile enumerate se pot schimba fara notificare prealabila.