



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Interstellar/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICE	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse SLR, composite, -5/+15mm offset
SEDEŽ	Giant Grit SL
POGON	
PRESTAVNE ROČICE	SRAM Force eTap AXS, 2x12
PREDNJI MENJALNIK	SRAM Force eTap AXS
ZADNJI MENJALNIK	SRAM Force eTap AXS
ZAVORE	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Force eTap AXS hydraulic
VERIŽNIK	SRAM Force, 12-speed, 10x36
VERIGA	SRAM Force D1
GONILKE Z VERIŽNIKI	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
PESTA	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	Sapim CX-Ray
PLAŠČI	CADEX GX, 700x40c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Dolžina sedežne cevi (mm)	430	450	470	490	510
Kot sedežne cevi	74,0°	73,5°	73,5°	73,0°	72,5°
Top Tube Length (mm)	540	550	560	575	585
Višina glave okvirja (mm)	125	135	150	165	175
Krmilni kot	70,0°	71,0°	71,5°	72,0°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	62 65
Medosna razdalja (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1036 1046
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	586	602	618
Doseg (mm)	381	381	387	391	396
Višina zgornje cevi (mm)	724 731	740 747	757 764	774 780	791 798
Širina krmila (mm)	420	420	440	440	460
Dolžina opore krmila (mm)	50	60	70	80	90
Dolžina gonilke (mm)	170	170	172,5	172,5	175
Velikost obročnikov	700c	700c	700c	700c	700c

Vse navedene specifikacije se lahko spremenijo brez obvestila.