

REVOLT ADVANCED PRO 0

GIANT



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Cyber Lime
RAM	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
GAFFEL	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SADELSTOLPE	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	Giant Grit SL
PEDALER	no pedal [GA, Pan-Eu], platform pedal [GU, GV, GJ]
DRIVLINÅ	
VÄXLAR	SRAM Force AXS E1, 2x12
FRAMVÄXEL	SRAM Force AXS D2
BAKVÄXEL	SRAM Force AXS E1
BROMSAR	SRAM Force AXS E1 hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
BROMSSPAKAR	SRAM Force AXS E1 hydraulic
KASSETT	SRAM Force E1, 12-speed, 10x36
KEDJA	SRAM Force E1
VEVPARTI	SRAM Force D2 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant CXR 1 WheelSystem, [F] 35mm, [R] 35mm
NAV	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Sapim CX-Ray
DÄCK	CADEX GX, 700x40c, tubeless
EXTRAFUNKTIONER	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 80 990,00 kr

GEOMETRY

RAM	S		M		L		XL	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Längd sadelrör (mm)	450		470		510		530	
Seat Post Insertion Depth (mm)	308		323		375		375	
Vinkel sadelrör	73,5°		73,5°		73,0°		73,0°	
Topprörets längd (mm)	550		560		585		600	
Styrhuvud Längd (mm)	135		150		180		195	
Vinkel styrhuvud	71,0°		71,5°		72,0°		72,0°	
Gaffelvinkel (mm)	50		50		50		50	
Spår (mm)	72 75		68 72		65 68		65 68	
Hjulbas (mm)	1020 1030		1026 1036		1041 1051		1056 1066	
Kedjestagslängd (mm)	425 435		425 435		425 435		425 435	
Nedre fäste Drop (mm)	80 81		80 81		80 81		80 81	
Stack (mm)	570		586		616		630	
Reach (mm)	381		387		397		407	
Stå över höjden (mm)	740 747		757 764		791 797		807 814	
Styrets bredd (mm)	420		440		460		460	
Stamlängd (mm)	60		70		80		90	
Vevlängd (mm)	170		172,5		175		175	

All specifications listed are subject to change without notice.