

REVOLT ADVANCED PRO 1



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Ocean Twilight/Chrome
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FORGAFFEL	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SADELPIND	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	Giant Grit SL
GEARGRUPPE	
SKIFTEGREB	SRAM Rival AXS E1, 2x12
FORSKIIFTER	SRAM Rival AXS D1
BAGSKIIFTER	SRAM Rival AXS E1
BREMSE	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BREMSEGREB	SRAM Rival AXS E1 hydraulic
KASSETTE	SRAM Rival D1, 12-speed, 10x36
KÆDE	SRAM Rival E1
KRANKSÆT	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
NAV	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
EGER	Sapim CX-Ray
DÆK	CADEX GX, 700x40c, tubeless
EKSTRA	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
GRÆNSER	
MAX DÆKSTØRRELSE	53mm

Pris: 44.999,00 kr.

GEOMETRI

RAMME	S M ML L XL					
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sadelrørslængde (mm)	450	470	490	510	530	
Sadelpindindsætningsdybde (mm)	308	323	363	375	375	
Sadelrørsvinkel	73,5°	73,5°	73,0°	73,0°	73,0°	
Overrørslængde (mm)	550	560	575	585	600	
Kronrørslængde (mm)	135	150	165	180	195	
Kronrørsvinkel	71,0°	71,5°	72,0°	72,0°	72,0°	
Forgaffel fremspring (rake) (mm)	50	50	50	50	50	
Sti (mm)	72 75	68 72	65 68	65 68	65 68	
Akselafstand (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066	
Kædestagslængde (mm)	425 435	425 435	425 435	425 435	425 435	
Krankboks drop (mm)	80 81	80 81	80 81	80 81	80 81	
Stack (mm)	570	586	602	616	630	
Reach (mm)	381	387	391	397	407	
Skridthøjde (mm)	740 747	757 764	774 780	791 797	807 814	
Styrbredde (mm)	420	440	440	460	460	
Frempindslængde (mm)	60	70	80	80	90	
Pedalarmslængde (mm)	170	172,5	172,5	175	175	

Alle de anførte specifikationer kan ændres uden varsel.