

REVOLT ADVANCED PRO 1



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Meteor Storm
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc, flat mount disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm XS, S:42cm, M, M/L:44cm, L, XL:46cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact AeroLight, -10 degree
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Giant Grit SL *some bikes may be substituted: Giant Approach SL
DRIVETRAIN	
SHIFTERS	SRAM Rival eTap AXS, 2x12
FRONT DERAILLEUR	SRAM Rival eTap AXS
REAR DERAILLEUR	SRAM Rival eTap AXS
BRAKES	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival eTap AXS
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAIN	SRAM Rival D1
CRANKSET	SRAM Rival D1 DUB, 30/43 XS, S:170mm, M, M/L:172.5mm, L, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 1 Carbon Disc WheelSystem, 35mm depth, 25mm inner width
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX GX, tubeless, 700x40c, 170 tpi, FOLDING
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, integrated down tube storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Suggested Retail Price (CDN): \$6,299.00

FRAME GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SH
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	190
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	400
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797	800
Handlebar Width (mm)	420	420	440	440	460	460
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700c	700c	700c	700c	700c	700c

All prices and specifications are subject to change without notice.