

REVOLT ADVANCED PRO 1

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Ocean Twilight/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Giant Grit SL
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS E1, 2x12
FRONT DERAILLEUR	SRAM Rival AXS D1
REAR DERAILLEUR	SRAM Rival AXS E1
BRAKES	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival AXS E1 hydraulic
CASSETTE	SRAM Rival D1, 12-speed, 10x36
CHAIN	SRAM Rival E1
CRANKSET	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TYRES	CADEX GX, 700x40c, tubeless
EXTRAS	Tubeless prepared, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position with 1x drivetrains. Max tyre size with a 2x drivetrain is 45mm in the long position.

Price: €4,799.00

GEOMETRY

FRAME	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	450	470	490	510	530
Seat Post Insertion Depth (mm)	308	323	363	375	375
Seat Tube Angle	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	550	560	575	585	600
Head Tube Length (mm)	135	150	165	180	195
Head Tube Angle	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	72 75	68 72	65 68	65 68	65 68
Wheelbase (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Stand Over Height (mm)	740 747	757 764	774 780	791 797	807 814
Handlebar Width (mm)	420	440	440	460	460
Stem Length (mm)	60	70	80	80	90
Crank Length (mm)	170	172.5	172.5	175	175

All specifications listed are subject to change without notice.