

REVOLT ADVANCED PRO 1



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLORS	Ocean Twilight
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, flat mount disc, flip chip dropout, integrated downtube storage
FORK	Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR D-Fuse, 31.8mm S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact Aerolight S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Giant Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS HRD, ED-Force-E1
FRONT DERAILLEUR	SRAM Rival AXS Wide D2
REAR DERAILLEUR	SRAM Rival AXS, RD-Force-E1
BRAKES	SRAM Rival AXS HRD, ED-Riv-E1, SRAM PaceLine rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Rival AXS HRD, ED-Riv-E1
CASSETTE	SRAM Rival E1 XG-1250, 12-speed, 10-36
CHAIN	SRAM Rival-E1, 12-speed
CRANKSET	SRAM Rival D1 Wide DUB , 30/43 S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
HUBS	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant alloy, 3-pawl 36t driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Sprint
TIRES	CADEX GX, 700x40c, tubeless
EXTRAS	Tubeless prepared, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position, In frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm in "long" flip chip position

Price: \$7,999.00

GEOMETRY

FRAME	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	430	450	470	490	510
Seat Post Insertion Depth (mm)	294	308	323	363	375
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585
Head Tube Length (mm)	125	135	150	165	180
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797
Stem Length (mm)	50	60	70	80	80
Crank Length (mm)	170	170	172.5	172.5	175

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.