

REVOLT ADVANCED PRO 1

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Blue Dragonfly/Chrome
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
TIJERA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
POTENCIA	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
POSTE DE ASIENTO	Giant D-Fuse SLR w/ offset -5/+15
ASIENTO	Giant Approach SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Sram Rival eTap AXS HRD 2x12
DESVIADOR	Sram Rival eTap AXS Wide
CAMBIO TRASERO	Sram Rival eTap AXS 36T
FRENOS	Sram RivalTap AXS HRD, SRAM Centerline rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	SRAM Rival AXS HRD (hydraulic road disc)
CASSETTE	SRAM Rival, XG-1270, 12-speed, 10-36
CADENA	SRAM Rival D1, 12-speed
MULTIPLICACIÓN	SRAM Rival D1 DUB,30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
MAZAS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
RAYOS	Sapim CX-Ray
NEUMÁTICOS	CADEX AR, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Precio: \$125,990.00

GEOMETRÍA

CUADRO	XS		S		M		ML	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	430		450		470		490	
Ángulo de la Base del Poste de Asiento	74.0°		73.5°		73.5°		73.0°	
Longitud del Tubo Superior (mm)	540		550		560		575	
Longitud del Telescopio (mm)	125		135		150		165	
Ángulo del Telescopio	70.0°		71.0°		71.5°		72.0°	
Rake (mm)	50		50		50		50	
Trail (mm)	78 82		72 75		68 72		65 68	
Distancia entre Ejes (mm)	1024 1034		1020 1030		1026 1036		1031 1041	
Longitud de Vaina Inferior (mm)	425 435		425 435		425 435		425 435	
Caída del Eje de Centro (mm)	80 81		80 81		80 81		80 81	
Stack (mm)	556		570		586		602	
Reach (mm)	381		381		387		391	
Altura del Tubo Superior al Suelo (mm)	724 731		740 747		757 764		774 780	
Ancho del Manubrio (mm)	420		420		440		440	
Longitud de la Potencia (mm)	50		60		70		80	
Longitud de la Biela (mm)	170		170		172.5		172.5	
Tamaño de las Ruedas	700C		700C		700C		700C	

Todas las especificaciones están sujetas a cambios sin previo aviso.