

REVOLT ADVANCED PRO 1



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Meteor Storm
CADRE	Advanced-grade composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPOSANTS	
CINTRE	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIGE DE SELLE	Giant D-Fuse SLR, composite, -5/+15mm offset
SELLE	Giant Grit SL
DÉRAILLEUR	
MANETTES	SRAM Rival eTap AXS, 2x12
DÉRAILLEUR AVANT	SRAM Rival eTap AXS
DÉRAILLEUR ARRIÈRE	SRAM Rival eTap AXS
FREINS	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
LEVIER DE FREIN	SRAM Rival eTap AXS hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAÎNE	SRAM Rival D1
PÉDALIER	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
MOYEUX	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Sapim CX-Ray
PNEUS	CADEX GX, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	53mm

Prix Public Conseillé: 5 800,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Longueur de tube de selle (mm)	430	450	470	490	510
Angle de tube de selle	74,0°	73,5°	73,5°	73,0°	73,0°
Longueur du tube supérieur (mm)	540	550	560	575	585
Longueur du tube de direction (mm)	125	135	150	165	180
Angle du tube de direction	70,0°	71,0°	71,5°	72,0°	72,0°
Déport de fourche (mm)	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68
Empattement (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 10
Longueur des bases (mm)	425 435	425 435	425 435	425 435	425 435
Drop du boîtier de pédalier (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Hauteur en statique (mm)	724 731	740 747	757 764	774 780	791 797
Largeur de cintre (mm)	420	420	440	440	460
Longueur de potence (mm)	50	60	70	80	80
Longueur des manivelles (mm)	170	170	172,5	172,5	175
Diamètre des roues	700c	700c	700c	700c	700c

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).