



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, M/L, L, XL
BOJE	Ocean Twilight/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
VOLAN	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
LULA VOLANA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
CIJEV SJEDALA	Giant D-Fuse SLR, composite, -5/+15mm offset
SJEDALO	Giant Grit SL
POGON	
RUČICE MJENJAČA	SRAM Rival AXS E1, 2x12
PREDNJI MJENJAČ	SRAM Rival AXS D1
STRAŽNJI MJENJAČ	SRAM Rival AXS E1
KOČNICE	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
RUČICE KOČNICA	SRAM Rival AXS E1 hydraulic
KAZETA	SRAM Rival D1, 12-speed, 10x36
LANAC	SRAM Rival E1
POGON	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
NABE	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	Sapim CX-Ray
GUME	CADEX GX, 700x40c, tubeless
DODACI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS			S			M		
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	
Dužina cijevi sjedala (mm)	430	450	450	470	470	490	490	510	
Kut cijevi sjedala	74,0°	73,5°	73,5°	73,5°	73,5°	73,5°	73,5°	73,5°	
Dužina gornje cijevi (mm)	540	550	550	560	560	570	570	580	
Dužina prednje cijevi (mm)	125	135	135	150	150	150	150	150	
Kut vilice	70,0°	71,0°	71,0°	71,5°	71,5°	71,5°	71,5°	71,5°	
Zakrivljenost vilice (offset) (mm)	50	50	50	50	50	50	50	50	
Staza (mm)	78 82	72 75	72 75	68 72	68 72	68 72	68 72	68 72	
Međuosovinski razmak kotača (mm)	1024 1034	1020 1030	1020 1030	1026 1036	1026 1036	1026 1036	1026 1036	1026 1036	
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	425 435	425 435	425 435	425 435	425 435	425 435	425 435	425 435	
Položaj osovine pogona (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	556	570	570	586	586	586	586	586	
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	381	381	381	387	387	387	387	387	
Prekoračna visina (mm)	724 731	740 747	740 747	757 764	757 764	757 764	757 764	757 764	
Širina volana (mm)	420	420	420	440	440	440	440	440	
Dužina lule volana (mm)	50	60	60	70	70	70	70	70	
Dužina poluge pedale (mm)	170	170	170	172,5	172,5	172,5	172,5	172,5	

Sve navedene specifikacije podložne su promjeni bez prethodne najave.