

REVOLT ADVANCED PRO 1



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Meteor Storm
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VOORVORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELPEN	Giant D-Fuse SLR, composite, -5/+15mm offset
ZADEL	Giant Grit SL
AFMONTAGE	
SHIFTERS	SRAM Rival eTap AXS, 2x12
VOORDERAILLEUR	SRAM Rival eTap AXS
ACHTERDERAILLEUR	SRAM Rival eTap AXS
REMMEN	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Rival eTap AXS hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x36
AANDRIJVING	SRAM Rival D1
CRANKSET	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAVEN	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim CX-Ray
BANDEN	CADEX GX, 700x40c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Adviesprijs: € 5.799,00

GEOMETRIE

FRAME	S	M	ML	L	XL
	SHORT LONG SHORT LONG SHORT LONG SHORT LONG SHORT LONG				
Zitbuis lengte (mm)	450	470	490	510	530
Zitbuis hoek	73,5°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	550	560	575	585	600
Balhoofdbuis Lengte (mm)	135	150	165	180	195
Balhoofdbuis Hoek	71,0°	71,5°	72,0°	72,0°	72,0°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	72 75	68 72	65 68	65 68	65 68
Wielbasis (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066
Liggende achtervork lengte (mm)	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Stand Over Height (mm)	740 747	757 764	774 780	791 797	807 814
Stuur breedte (mm)	420	440	440	460	460
Stuurpen Lengte (mm)	60	70	80	80	90
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700c	700c	700c	700c	700c

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.