

REVOLT ADVANCED PRO 1

GIANT



SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L, XL
CORES	Ocean Twilight/Chrome
QUADRO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FORQUILHA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTES	
GUIADOR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
PUNHOS	Stratus Lite 3.0
AVANÇO	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ESPIGÃO DE SELIM	Giant D-Fuse SLR, composite, -5/+15mm offset
SELIM	Giant Grit SL
TRANSMISSÃO	
MANETES	SRAM Rival AXS E1, 2x12
DESVIADOR DIANTEIRO	SRAM Rival AXS D1
DESVIADOR TRASEIRO	SRAM Rival AXS E1
TRAVÕES	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
MANÍPULOS DOS TRAVÕES	SRAM Rival AXS E1 hydraulic
CASSETTE	SRAM Rival D1, 12-speed, 10x36
CORRENTE	SRAM Rival E1
CONJUNTO PEDALEIRO	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
CUBOS	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
RAIOS	Sapim CX-Ray
PNEUS	CADEX GX, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITES	
FOLGA MÁXIMA DO PNEU	53mm

Preço: 4 849,00 €

GEOMETRIA

QUADRO	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Comprimento do tubo do assento (mm)	430	450	470	490	510
Seat Post Insertion Depth (mm)	294	308	323	363	375
Ângulo do tubo do assento	74,0°	73,5°	73,5°	73,0°	73,0°
Comprimento do tubo superior (mm)	540	550	560	575	585
Comprimento do tubo principal (mm)	125	135	150	165	180
Ângulo do tubo principal	70,0°	71,0°	71,5°	72,0°	72,0°
Garfo ancinho (mm)	50	50	50	50	50
Trilha (mm)	78 82	72 75	68 72	65 68	65 68
distância entre eixos (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051
Comprimento Chain Stay (mm)	425 435	425 435	425 435	425 435	425 435
Suporte inferior (mm)	80 81	80 81	80 81	80 81	80 81
Pilha (mm)	556	570	586	602	616
Alcançar (mm)	381	381	387	391	397
Altura do standover (mm)	724 731	740 747	757 764	774 780	791 797
Largura do guidão (mm)	420	420	440	440	460
Comprimento da haste (mm)	50	60	70	80	80
Comprimento da Manivela (mm)	170	170	172,5	172,5	175

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.