

REVOLT ADVANCED PRO 1

GIANT



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, M/L, L, XL
FARBY	Ocean Twilight/Chrome
RÁM	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VIDLICA	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTY	
RIADIDLÁ	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPY	Stratus Lite 3.0
PREDSTAVEC	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SEDOVKA	Giant D-Fuse SLR, composite, -5/+15mm offset
SEDADLO	Giant Grit SL
POHON	
RADENIE	SRAM Rival AXS E1, 2x12
PREŠMYKAČ	SRAM Rival AXS D1
PREHADZOVAČKA	SRAM Rival AXS E1
BRZDY	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRZDOVÉ PÁKY	SRAM Rival AXS E1 hydraulic
KAZETA	SRAM Rival D1, 12-speed, 10x36
REŤAZ	SRAM Rival E1
KLUKY	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
NÁBOJE	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
ŠPICE	Sapim CX-Ray
PNEUMATIKY	CADEX GX, 700x40c, tubeless
DOPLNKY	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	53mm

Cena: 5 599 €

GEOMETRIA

RÁM	XS	S	M	ML
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Dĺžka sedlovej trubky (mm)	430	450	470	490
Hĺbka vloženia sedlovky (mm)	294	308	323	363
Uhol sedlovej trubky	74,0°	73,5°	73,5°	73,0°
Dĺžka hornej rámovej trubky (mm)	540	550	560	575
Dĺžka hlavovej trubky (mm)	125	135	150	165
Uhol hlavovej trubky	70,0°	71,0°	71,5°	72,0°
Offset vidlice (mm)	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68
Rázvor (mm)	1024 1034	1020 1030	1026 1036	1031 1041
Dĺžka zadnej stavby (mm)	425 435	425 435	425 435	425 435
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80 81	80 81	80 81	80 81
Stack - výška riadenia (mm)	556	570	586	602
Reach (mm)	381	381	387	391
Výška rámu od zeme (mm)	724 731	740 747	757 764	774 780
Šírka riaditok (mm)	420	420	440	440
Dĺžka predstavca (mm)	50	60	70	80
Dĺžka klúk (mm)	170	170	172,5	172,5

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.