

REVOLT ADVANCED PRO 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Ocean Twilight/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VILICE	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse SLR, composite, -5/+15mm offset
SEDEŽ	Giant Grit SL
POGON	
PRESTAVNE ROČICE	SRAM Rival AXS E1, 2x12
PREDNJI MENJALNIK	SRAM Rival AXS D1
ZADNJI MENJALNIK	SRAM Rival AXS E1
ZAVORE	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Rival AXS E1 hydraulic
VERIŽNIK	SRAM Rival D1, 12-speed, 10x36
VERIGA	SRAM Rival E1
GONILKE Z VERIŽNIKI	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
PESTA	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	Sapim CX-Ray
PLAŠČI	CADEX GX, 700x40c, tubeless
DODATKI	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS	S	M	ML	
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	S
Dolžina sedežne cevi (mm)	430	450	470	490	5
Seat Post Insertion Depth (mm)	294	308	323	363	3
Kot sedežne cevi	74,0°	73,5°	73,5°	73,0°	7
Top Tube Length (mm)	540	550	560	575	5
Višina glave okvirja (mm)	125	135	150	165	1
Krmilni kot	70,0°	71,0°	71,5°	72,0°	7
Zamik vpetja osi (mm)	50	50	50	50	5
Trail (mm)	78 82	72 75	68 72	65 68	6
Medosna razdalja (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	425 435	4
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	8
Oddaljenost zgornje cevi od gonilne osi (mm)	556	570	586	602	6
Doseg (mm)	381	381	387	391	3
Višina zgornje cevi (mm)	724 731	740 747	757 764	774 780	7
Širina krmila (mm)	420	420	440	440	4
Dolžina opore krmila (mm)	50	60	70	80	8
Dolžina gonilke (mm)	170	170	172,5	172,5	1

Vse navedene specifikacije se lahko spremenijo brez obvestila.