

REVOLT ADVANCED PRO 1



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Meteor Storm
RAM	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
GAFFEL	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SADELSTOLPE	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	Giant Grit SL
DRIVLINÄ	
VÄXLAR	SRAM Rival eTap AXS, 2x12
FRAMVÄXEL	SRAM Rival eTap AXS
BAKVÄXEL	SRAM Rival eTap AXS
BROMSAR	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BROMSSPAKAR	SRAM Rival eTap AXS hydraulic
KASSETT	SRAM Rival, 12-speed, 10x36
KEDJA	SRAM Rival D1
VEVPARTI	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAV	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Sapim CX-Ray
DÄCK	CADEX GX, 700x40c, tubeless
EXTRAFUNKTIONER	tubeless prepared, 53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 68 290,00 kr

GEOMETRY

RAM	M
	SHORT LONG
Längd sadelrör (mm)	470
Vinkel sadelrör	73,5°
Topprörets längd (mm)	560
Styrhuvud Längd (mm)	150
Vinkel styrhuvud	71,5°
Gaffelvinkel (mm)	50
Spår (mm)	68 72
Hjulbas (mm)	1026 1036
Kedjestagslängd (mm)	425 435
Nedre fäste Drop (mm)	80 81
Stack (mm)	586
Reach (mm)	387
Stå över höjden (mm)	757 764
Styrets bredd (mm)	440
Stamlängd (mm)	70
Vevlängd (mm)	172,5
Hjulstorlek	700c

All specifications listed are subject to change without notice.