

REVOLT ADVANCED PRO 1



產品規格

車架	
尺寸	XS, S, M,
顏色	Ocean Twilight/Chrome
車架	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
前叉	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
車把手	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
把手帶/套	Stratus Lite 3.0
暨桿	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
座桿	Giant D-Fuse SLR, composite, -5/+15mm offset
坐墊	Giant Grit SL
DRIVETRAIN	
變速把手	SRAM Rival AXS E1, 2x12
前變速器	SRAM Rival AXS D1
後變速器	SRAM Rival AXS E1
煞車系統	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
煞車把手	SRAM Rival AXS E1 hydraulic
飛輪	SRAM Rival D1, 12-speed, 10x36
鏈條	SRAM Rival E1
大齒盤	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET (B B)	SRAM DUB, press fit

輪組	
輪圈	Giant CXR 2 WheelSystem, [F] 35mm, [R] 35mm
花鼓	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
輻條	Sapim CX-Ray
外胎	CADEX GX, 700x40c, tubeless
其他	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Price: NT\$128,000

車架幾何

車架	XS	S	M	ML
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
座(立)管長 (mm)	430	450	470	490
Seat Post Insertion Depth (mm)	294	308	323	363
座(立)管角度	74.0°	73.5°	73.5°	73.0°
上管長度 (mm)	540	550	560	575
頭管長度 (mm)	125	135	150	165
頭管角度	70.0°	71.0°	71.5°	72.0°
前叉 (mm)	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68
前後輪距 (mm)	1024 1034	1020 1030	1026 1036	1031 1041
後下叉長度 (mm)	425 435	425 435	425 435	425 435
五通下降高度 (mm)	80 81	80 81	80 81	80 81
頭碗至五通高度 (mm)	556	570	586	602
頭碗至五通長度 (mm)	381	381	387	391
上管至地面高度 (mm)	724 731	740 747	757 764	774 780
把手寬 (mm)	420	420	440	440
龍頭長度 (mm)	50	60	70	80
曲柄長度 (mm)	170	170	172.5	172.5

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。