



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Slate
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
FORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset

WHEELS	
EXTRAS	53mm max tire size in "long" flip chip position, 53mm max tire size in "short" flip chip position, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	195
Head Tube Angle	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68
Wheelbase (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051 1061
Chain Stay Length (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Stand Over Height (mm)	724 731	740 747	757 764	774 780	791 797	807 814
Handlebar Width (mm)	420	420	440	440	460	460
Stem Length (mm)	50	60	70	80	80	90
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700c	700c	700c	700c	700c	700c

All specifications listed are subject to change without notice.