

REVOLT ADVANCED SL 0



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Raw Carbon / Prism Mist
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORGAFFEL	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SADELPIND	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SADEL	CADEX Amp
GEARGRUPPE	
SKIFTEGREB	SRAM RED XPLR AXS E1, 1x13
BAGSKIFTER	SRAM RED XPLR AXS E1
BREMSE	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
BREMSEGREB	SRAM RED E1 hydraulic
KASSETTE	SRAM RED E1, 13-speed, 10x46
KÆDE	SRAM RED E1
KRANKSÆT	SRAM RED XPLR AXS with power meter, 44t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KRANKBOKS	SRAM DUB, Press Fit

HJUL	
FÆLGE	CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NAV	[F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes
EGER	CADEX Super Aero Carbon Spoke
DÆK	CADEX GXR, 700x45c, tubeless
EKSTRA	tubeless prepared, computer mount, chain guide
GRÆNSER	
MAX DÆKSTØRRELSE	700x53mm
MAX KLINGE STØRRELSE	54T

Pris: 78.999,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørslængde (mm)	450	470	490	510	530
Sadelrørvinkel	74,5°	74,5°	74,0°	74,0°	74,0°
Overrørslængde (mm)	540	550	565	580	590
Kronrørslængde (mm)	100	120	135	155	180
Kronrørvinkel	71,0°	71,5°	72,0°	72,0°	72,0°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	74	71	67	67	67
Akselafstand (mm)	1027	1033	1039	1055	1066
Kædestagslængde (mm)	433	433	433	433	433
Krankboks drop (mm)	80	80	80	80	80
Stack (mm)	536	557	573	592	616
Reach (mm)	391	395	401	410	413
Skridthøjde (mm)	743	762	779	798	818
Styrbredde (mm)	380	400	400	420	420
Frempindslængde (mm)	80	90	100	100	110
Pedalarmslængde (mm)	165	170	170	172,5	172,5
Hjulstørrelse	700C	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.