

REVOLT ADVANCED SL 0

GIANT



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, ML, L, XL
FARBE	Raw Carbon / Prism Mist
RAHMEN	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
GABEL	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SATTELSTÜTZE	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SATTEL	CADEX Amp
ANTRIEB	
SCHALTHEBEL	SRAM RED XPLR AXS E1, 1x13
SCHALTWERK	SRAM RED XPLR AXS E1
BREMSSEN	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
BREMSHEBEL	SRAM RED E1 hydraulic
KASSETTE	SRAM RED E1, 13-speed, 10x46
KETTE	SRAM RED E1
KURBEL	SRAM RED XPLR AXS with power meter, 44t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
TRETLAGER	SRAM DUB, Press Fit

LAUFRÄDER	
FELGEN	CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NABE	[F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes
SPEICHEN	CADEX Super Aero Carbon Spoke
REIFEN	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	700x53mm
MAX CHAINRING SIZE	54T

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	75.0°	74.5°	74.5°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	530	540	550	565	580	590
Steuerrohr-Länge (mm)	90	100	120	135	155	180
Steuerrohr-Winkel	70.5°	71.0°	71.5°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	78	74	71	67	67	67
Radstand (mm)	1026	1027	1033	1039	1055	1066
Kettenstreben-Länge (mm)	433	433	433	433	433	433
Tretlager-Höhe (mm)	80	80	80	80	80	80
Stack (mm)	525	536	557	573	592	616
Reach (mm)	389	391	395	401	410	413
Überstandshöhe (mm)	726	743	762	779	798	818
Lenkerbreite (mm)	380	380	400	400	420	420
Vorbaulänge (mm)	70	80	90	100	100	110
Kurbellänge (mm)	165	165	170	170	172.5	172.5
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.