

REVOLT ADVANCED SL 0

GIANT



SPECS

FRAME	
SIZES	XS, S, M, ML, L, XL
COLORS	Raw Carbon / Prism Mist
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORK	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SEATPOST	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SADDLE	CADEX Amp
DRIVETRAIN	
SHIFTERS	SRAM RED XPLR AXS E1, 1x13
REAR DERAILLEUR	SRAM RED XPLR AXS E1
BRAKES	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM RED E1 hydraulic
CASSETTE	SRAM RED E1, 13-speed, 10x46
CHAIN	SRAM RED E1
CRANKSET	SRAM RED XPLR AXS with power meter, 44t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
HUBS	[F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes
SPOKES	CADEX Super Aero Carbon Spoke
TIRES	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	700x53mm
MAX CHAINRING SIZE	54T

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (inch)	16.9	17.7	18.5	19.3	20.1	20.9
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°	74.0°	74.0°
Top Tube Length (inch)	20.9	21.3	21.7	22.2	22.8	23.2
Head Tube Length (inch)	3.5	3.9	4.7	5.3	6.1	7.1
Head Tube Angle	70.5°	71.0°	71.5°	72.0°	72.0°	72.0°
Fork Rake (inch)	2	2	2	2	2	2
Trail (inch)	3.1	2.9	2.8	2.6	2.6	2.6
Wheelbase (inch)	40.4	40.4	40.7	40.9	41.5	42
Chain Stay Length (inch)	17	17	17	17	17	17
Bottom Bracket Drop (inch)	3.1	3.1	3.1	3.1	3.1	3.1
Stack (inch)	20.7	21.1	21.9	22.6	23.3	24.3
Reach (inch)	15.3	15.4	15.6	15.8	16.1	16.3
Stand Over Height (inch)	28.6	29.3	30	30.7	31.4	32.2
Handlebar Width (inch)	15	15	15.7	15.7	16.5	16.5
Stem Length (inch)	2.8	3.1	3.5	3.9	3.9	4.3
Crank Length (inch)	6.5	6.5	6.7	6.7	6.8	6.8
Wheel Size	700C	700C	700C	700C	700C	700C

**All specifications and prices listed are subject to change without notice.
Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*