

# REVOLT ADVANCED SL 0



## SPECS

| RAMME          |                                                                                                                  |
|----------------|------------------------------------------------------------------------------------------------------------------|
| STØRRELSE      | XS, S, M, ML, L, XL                                                                                              |
| FARGE          | Raw Carbon / Prism Mist                                                                                          |
| RAMME          | Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout                                               |
| GAFFEL         | Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc                     |
| KOMPONENTER    |                                                                                                                  |
| STYRE          | Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm |
| GRIPS          | Stratus Lite 3.0                                                                                                 |
| STYRSTEM       | Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110                                      |
| SETEPINNE      | Giant Contact SLR XR D-Fuse, composite, 20mm offset                                                              |
| SADEL          | CADEX Amp                                                                                                        |
| DRIVVERK       |                                                                                                                  |
| GIRHENDLER     | SRAM RED XPLR AXS E1, 1x13                                                                                       |
| BAKGIR         | SRAM RED XPLR AXS E1                                                                                             |
| BREMSE         | SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm                                             |
| BREMSEHENDLER  | SRAM RED E1 hydraulic                                                                                            |
| KASSETT        | SRAM RED E1, 13-speed, 10x46                                                                                     |
| KJEDE          | SRAM RED E1                                                                                                      |
| KRANK          | SRAM RED XPLR AXS with power meter, 44t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm             |
| BOTTOM BRACKET | SRAM DUB, Press Fit                                                                                              |

| HJUL               |                                                                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FELG               | CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm                                                                                              |
| NAV                | [F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes |
| EIKE               | CADEX Super Aero Carbon Spoke                                                                                                                               |
| DEKK               | CADEX GXR, 700x45c, tubeless                                                                                                                                |
| EXTRAS             | tubeless prepared, computer mount, chain guide                                                                                                              |
| LIMITS             |                                                                                                                                                             |
| MAX TIRE CLEARANCE | 700x53mm                                                                                                                                                    |
| MAX CHAINRING SIZE | 54T                                                                                                                                                         |

## GEOMETRI

| RAMME                    | XS    | S     | M     | ML    | L     | XL    |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 430   | 450   | 470   | 490   | 510   | 530   |
| Seat Tube Angle          | 75,0° | 74,5° | 74,5° | 74,0° | 74,0° | 74,0° |
| Top Tube Length (mm)     | 530   | 540   | 550   | 565   | 580   | 590   |
| Head Tube Length (mm)    | 90    | 100   | 120   | 135   | 155   | 180   |
| Head Tube Angle          | 70,5° | 71,0° | 71,5° | 72,0° | 72,0° | 72,0° |
| Fork Rake (mm)           | 50    | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)               | 78    | 74    | 71    | 67    | 67    | 67    |
| Wheelbase (mm)           | 1026  | 1027  | 1033  | 1039  | 1055  | 1066  |
| Chain Stay Length (mm)   | 433   | 433   | 433   | 433   | 433   | 433   |
| Bottom Bracket Drop (mm) | 80    | 80    | 80    | 80    | 80    | 80    |
| Stack (mm)               | 525   | 536   | 557   | 573   | 592   | 616   |
| Reach (mm)               | 389   | 391   | 395   | 401   | 410   | 413   |
| Stand Over Height (mm)   | 726   | 743   | 762   | 779   | 798   | 818   |
| Handlebar Width (mm)     | 380   | 380   | 400   | 400   | 420   | 420   |
| Stem Length (mm)         | 70    | 80    | 90    | 100   | 100   | 110   |
| Crank Length (mm)        | 165   | 165   | 170   | 170   | 172,5 | 172,5 |
| Wheel Size               | 700C  | 700C  | 700C  | 700C  | 700C  | 700C  |

Alle spesifikasjonene kan endres uten varsel.