

REVOLT ADVANCED SL 0

GIANT



SPECS

QUADRO	
TAMANHOS	XS, S, M, ML, L, XL
CORES	Raw Carbon / Prism Mist
QUADRO	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORQUILHA	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTES	
GUIADOR	Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm
PUNHOS	Stratus Lite 3.0
AVANÇO	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
ESPIGÃO DE SELIM	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SELIM	CADEX Amp
TRANSMISSÃO	
MANETES	SRAM RED XPLR AXS E1, 1x13
DESVIADOR TRASEIRO	SRAM RED XPLR AXS E1
TRAVÕES	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
MANÍPULOS DOS TRAVÕES	SRAM RED E1 hydraulic
CASSETE	SRAM RED E1, 13-speed, 10x46
CORRENTE	SRAM RED E1
CONJUNTO PEDALEIRO	SRAM RED XPLR AXS with power meter, 44t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
MOVIMENTO CENTRAL	SRAM DUB, Press Fit

RODAS	
AROS	CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
CUBOS	[F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes
RAIOS	CADEX Super Aero Carbon Spoke
PNEUS	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITES	
FOLGA MÁXIMA DO PNEU	700x53mm
TAMANHO MÁXIMO DA COROA	54T

Preço: 8 799,00 €

GEOMETRIA

QUADRO	XS	S	M	ML	L	XL
Comprimento do tubo do assento (mm)	430	450	470	490	510	530
Ângulo do tubo do assento	75,0°	74,5°	74,5°	74,0°	74,0°	74,0°
Comprimento do tubo superior (mm)	530	540	550	565	580	590
Comprimento do tubo principal (mm)	90	100	120	135	155	180
Ângulo do tubo principal	70,5°	71,0°	71,5°	72,0°	72,0°	72,0°
Garfo ancinho (mm)	50	50	50	50	50	50
Trilha (mm)	78	74	71	67	67	67
distância entre eixos (mm)	1026	1027	1033	1039	1055	1066
Comprimento Chain Stay (mm)	433	433	433	433	433	433
Suporte inferior (mm)	80	80	80	80	80	80
Pilha (mm)	525	536	557	573	592	616
Alcançar (mm)	389	391	395	401	410	413
Altura do standover (mm)	726	743	762	779	798	818
Largura do guidão (mm)	380	380	400	400	420	420
Comprimento da haste (mm)	70	80	90	100	100	110
Comprimento da Manivela (mm)	165	165	170	170	172,5	172,5
Tamanho da roda	700C	700C	700C	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.