

REVOLT ADVANCED SL 0

GIANT



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, ML, L, XL
FARBY	Raw Carbon / Prism Mist
RÁM	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
VIDLICA	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
KOMPONENTY	
RIADIDLÁ	Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm
GRIPY	Stratus Lite 3.0
PREDSTAVEC	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SEDOVKA	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SEDADLO	CADEX Amp
POHON	
RADENIE	SRAM RED XPLR AXS E1, 1x13
PREHADZOVAČKA	SRAM RED XPLR AXS E1
BRZDY	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
BRZDOVÉ PÁKY	SRAM RED E1 hydraulic
KAZETA	SRAM RED E1, 13-speed, 10x46
REŤAZ	SRAM RED E1
KLUKY	SRAM RED XPLR AXS with power meter, 44t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
STREDOVÉ ZLOŽENIE	SRAM DUB, Press Fit

KOLESÁ	
RÁFIKY	CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
NÁBOJE	[F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes
ŠPICE	CADEX Super Aero Carbon Spoke
PNEUMATIKY	CADEX GXR, 700x45c, tubeless
DOPLNKY	tubeless prepared, computer mount, chain guide
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	700x53mm
MAXIMÁLNA VEĽKOSŤ REŤAZE	54T

Cena: 11 999 €

GEOMETRIA

RÁM	XS	S	M	ML	L	XL
Dĺžka sedlovej trubky (mm)	430	450	470	490	510	530
Uhol sedlovej trubky	75,0°	74,5°	74,5°	74,0°	74,0°	74,0°
Dĺžka hornej rámovej trubky (mm)	530	540	550	565	580	590
Dĺžka hlavovej trubky (mm)	90	100	120	135	155	180
Uhol hlavovej trubky	70,5°	71,0°	71,5°	72,0°	72,0°	72,0°
Offset vidlice (mm)	50	50	50	50	50	50
Trail (mm)	78	74	71	67	67	67
Rázvor (mm)	1026	1027	1033	1039	1055	1066
Dĺžka zadnej stavby (mm)	433	433	433	433	433	433
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80	80	80	80	80	80
Stack - výška riadenia (mm)	525	536	557	573	592	616
Reach (mm)	389	391	395	401	410	413
Výška rámu od zeme (mm)	726	743	762	779	798	818
Šírka riaditok (mm)	380	380	400	400	420	420
Dĺžka predstavca (mm)	70	80	90	100	100	110
Dĺžka klúk (mm)	165	165	170	170	172,5	172,5
Rozmer kolies	700C	700C	700C	700C	700C	700C

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.