

REVOLT ADVANCED SL 0



產品規格

車架	
尺寸	XS, S, M, ML, L, XL
顏色	Raw Carbon / Prism Mist
車架	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
前叉	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
車把手	Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm
把手帶/套	Stratus Lite 3.0
豎桿	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
座桿	Giant Contact SLR XR D-Fuse, composite, 20mm offset
坐墊	CADEX Amp
DRIVETRAIN	
變速把手	SRAM RED XPLR AXS E1, 1x13
後變速器	SRAM RED XPLR AXS E1
煞車系統	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
煞車把手	SRAM RED E1 hydraulic
飛輪	SRAM RED E1, 13-speed, 10x46
鍊條	SRAM RED E1
大齒盤	SRAM RED XPLR AXS with power meter, 44t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET (B B)	SRAM DUB, Press Fit

輪組	
輪圈	CADEX Max GXR WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
花鼓	[F] CADEX R3, Center Lock, one-piece integrated hub and spokes, [R] CADEX R3-C60, 60-tooth ratchet driver, Center Lock, one-piece integrated hub and spokes
輻條	CADEX Super Aero Carbon Spoke
外胎	CADEX GXR, 700x45c, tubeless
其他	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	700x53mm
MAX CHAINRING SIZE	54T

Price: NT\$308,000

車架幾何

車架	XS	S	M	ML
座(立)管長 (mm)	430	450	470	490
座(立)管角度	75.0°	74.5°	74.5°	74.0°
上管長度 (mm)	530	540	550	565
頭管長度 (mm)	90	100	120	135
頭管角度	70.5°	71.0°	71.5°	72.0°
前叉 (mm)	50	50	50	50
Trail (mm)	78	74	71	67
前後輪距 (mm)	1026	1027	1033	1039
後下叉長度 (mm)	433	433	433	433
五通下降高度 (mm)	80	80	80	80
頭碗至五通高度 (mm)	525	536	557	573
頭碗至五通長度 (mm)	389	391	395	401
上管至地面高度 (mm)	726	743	762	779
把手寬 (mm)	380	380	400	400
龍頭長度 (mm)	70	80	90	100
曲柄長度 (mm)	165	165	170	170
輪組尺寸	700C	700C	700C	700C

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。