

REVOLT ADVANCED SL 1

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Tempest Purple
CUADRO	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
HORQUILLA	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTES	
MANILLAR	Giant Contact SLR XR Integrated XS:420/380mm, S:420/380mm, M:440/400mm, M/L:440/400mm, L:440/420mm, XL:460/420mm
PUÑOS	Stratus Lite 3.0
POTENCIA	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
TIJA DE SILLÍN	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SILLÍN	Giant Grit SLR
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Force XPLR AXS E1, 1x13
CAMBIO TRASERO	SRAM Force XPLR AXS E1
FRENOS	SRAM Force AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	SRAM Force E1 hydraulic
CASETTE	SRAM Force E1, 13-speed, 10x46
CADENA	SRAM Force E1
JGO. PLATOS Y BIELAS	SRAM Force XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
BUJES	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
RADIOS	Aero Bladed Carbon Spoke
CUBIERTAS	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	700x53mm
MÁXIMO TAMAÑO DE PLATO	54t

Precio: 7.599,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud del tubo del sillín (mm)	430	450	470	490	510	530
Ángulo del tubo del sillín	75,0°	74,5°	74,5°	74,0°	74,0°	74,0°
Longitud del tubo superior (mm) (mm)	530	540	550	565	580	590
Longitud del tubo de dirección (mm) (mm)	90	100	120	135	155	180
Ángulo del tubo de dirección	70,5°	71,0°	71,5°	72,0°	72,0°	72,0°
Inclinación de la horquilla (mm)	50	50	50	50	50	50
Trail (mm) (mm)	78	74	71	67	67	67
Distancia entre ejes (mm) (mm)	1026	1027	1033	1039	1055	1066
Longitud de la vaina (mm) (mm)	433	433	433	433	433	433
Caída del eje de pedalier (mm) (mm)	80	80	80	80	80	80
Stack (mm) (mm)	525	536	557	573	592	616
Reach (mm) (mm)	389	391	395	401	410	413
Altura del suelo al tubo (mm) (mm)	726	743	762	779	798	818
Ancho del manillar (mm) (mm)	380	380	400	400	420	420
Longitud de la potencia (mm) (mm)	70	80	90	100	100	110
Longitud de las bielas (mm) (mm)	165	165	170	170	172,5	172,5
Tamaño de ruedas	700C	700C	700C	700C	700C	700C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.