

REVOLT ADVANCED SL 1



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Tempest Purple
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc, UDH dropout
FORK	Advanced SL-grade composite, full-composite, updated OverDrive steerer, 12mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR XR Integrated XS:70x420mm, S:80x420mm, M:90x440mm, M/L:100x440mm, L:100x440mm, XL:110x460mm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact SLR XR Integrated XS:70, S:80mm, M:90, M/L:100, L:100, XL:110
SEATPOST	Giant Contact SLR XR D-Fuse, composite, 20mm offset
SADDLE	Giant Grit SLR
DRIVETRAIN	
SHIFTERS	SRAM Force XPLR AXS E1, 1x13
REAR DERAILLEUR	SRAM Force XPLR AXS E1
BRAKES	SRAM Force AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force E1 hydraulic
CASSETTE	SRAM Force E1, 13-speed, 10x46
CHAIN	SRAM Force E1
CRANKSET	SRAM Force XPLR AXS with power meter, 42t XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant CXR 0 WheelSystem, hookless, carbon [F] 50mm, [R] 50mm
HUBS	[F] Giant Low Friction Aero Hub, Center Lock [R] Giant Low Friction Aero Hub, 60-tooth ratchet driver, Center Lock
SPOKES	Aero Bladed Carbon Spoke
TIRES	CADEX GXR, 700x45c, tubeless
EXTRAS	tubeless prepared, computer mount, chain guide
LIMITS	
MAX TIRE CLEARANCE	700x53mm
MAX CHAINRING SIZE	54t

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	75,0°	74,5°	74,5°	74,0°	74,0°	74,0°
Top Tube Length (mm)	530	540	550	565	580	590
Head Tube Length (mm)	90	100	120	135	155	180
Head Tube Angle	70,5°	71,0°	71,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78	74	71	67	67	67
Wheelbase (mm)	1026	1027	1033	1039	1055	1066
Chain Stay Length (mm)	433	433	433	433	433	433
Bottom Bracket Drop (mm)	80	80	80	80	80	80
Stack (mm)	525	536	557	573	592	616
Reach (mm)	389	391	395	401	410	413
Stand Over Height (mm)	726	743	762	779	798	818
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	70	80	90	100	100	110
Crank Length (mm)	165	165	170	170	172,5	172,5
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.